

Ultrasonic Cleaner

Features:

- ❖ Convenient preset function of heating and timer
- ❖ HF frequency 40 kHz
- ❖ Temperature range from ambient to 80°C
- ❖ Bottom-mounted drain valve
- ❖ Maximum 99 minutes cleaning time
- ❖ Microprocessor control: timer, temperature and output control
- ❖ LCD display



Technical Specifications

Technical Specifications						
Model	UC-10	UC-15	UC-22	UC-30	UC-22M	UC-34M
Volume Liter	10	15	22	30	22	34
Temperature Range	Ambient + 5°C to 80°C					
Ultrasonic Frequency	40 KHz				40/80/120 KHz	
Temperature Controller	Digital, PID Microcontroller with Auto Tuning					
Timer Max.	99 Min 59 Sec				59 MIN 59 SEC	
Ultrasonic Power Watt	240	300	480	600	360	900
Heating Power Watt	300	400	500	500	500	800
Degassing Function	Yes					
Power Adjustment Function	Yes					
Dimension Bath mm	300x240x150	330x300x150	500x300x150	500x300x200	500x300x150	650x350x150
Dimension outer mm	368x270x290	397x320x317	560x320x317	560x320x385	-----	-----
Material	Bath, Cover and Outer: SS 304					
Net Weight Kg	10	15	15	16	15	16